

# RME – Perstorp BioCaleo™



## Description

- RME – Perstorp BioCaleo™ meets the sustainability criteria according to Swedish regulation and EU-RED
- Meets the minimum requirements according to EN 14214
- Biodegradable and non ADR, i.e. easy to handle
- Storage stable up to 12 Months
- Liquid to -11°C

## Applications

- RME can be used to replace fossil diesel in heating applications

## Typical data of analysis\*

Purity, % (m/m)	98
Monoglyceride content, % (m/m)	0.3
Water content, mg/kg	<300
Alkali metals (Na+K), mg/kg	<2
Earth metals (Ca+Mg), mg/kg	<2
Phosphorus, mg/kg	<1
Total Contamination, mg/kg	<5
CFPP summer/winter, °C	-11/-20 <sup>1</sup>
Density at 15°C, kg/m <sup>3</sup>	883
Flash point, °C	120
Cetane number, -	52
Heat value effective, MJ/kg	38
Greenhouse gas reduction, %	>50 <sup>2</sup>

\*Normal analysed values of the product during a longer period of time

<sup>1</sup> According to agreement between both parties, minor deviations can occur

CAS no.: 67762-38-3

EC (EINECS) no.: 267-015-4

Valid from: March 9, 2016